



## Installation Instructions

Rock-Rails

07-15 Jeep JK Wrangler

Part Numbers:

J072RKR/J074RKR

**Please read instructions entirely before installing product. It is recommended to have assistance while performing the install.**

**This part uses the nuts located in the body mounts and does not require additional hardware.**

### **Tools Needed:**

Torque Wrench Ratchet 18mm Socket

**Step 1.** Locate the front and rear body buckets where the body mounts to the frame. **NOTE:** There are three body buckets per side.

**Step 2.** Start with the driver side. **NOTE:** The end with the cap is the rear of the bar.

**Step 3.** Remove the smaller nuts next to each large body mount washer on the front and rear body mount.

**Step 4.** Locate the Rock Rail's front mount and rear mount.

**Step 5.** Slide the Rock Rail over the large body mount washers in the front and rear body buckets.

**Step 6.** Take the nuts removed from the body buckets and loosely bolt the Rock Rail on.

**Step 7.** Once all four nuts are in place, tighten to 30 lbs.

**Step 8.** Repeat this process on the opposite side.

**Step 9.** If you have the detachable steps (part # JPTS32) you can bolt one per side at this time.

Products Licensed to N-FAB Inc. by Fichter Designs are protected by US Patent Law and International Copyright Law. Protected Patents include US Patent #6588783, #6874801, #7416202. Other patents and continuances pending. N-FAB product configurations also protected by International Trade Dress Law. All Designs and Patent infringements will be prosecuted to the full extent of the law.