

Rear Fender Base SKU: JK1001

2007-2015 Jeep JK 4 Door

SAFETY

Your safety and the safety of others is very important.

- In order to help you make informed decisions about safety, we have provided installation instructions and other information.
- These instructions alert you to potential hazards that could hurt you or others.
- Please do a job safety analysis (JSA) before each task to identify potential hazards for your situation and remove/protect against them.
- You must use your own good judgment, and take your time.

Read and understand all safety precautions and instructions before installing this product.

THIS PRODUCT IS FOR OFFROAD USE ONLY. ALL LIABILITY FOR INSTALLATION AND USE RESTS WITH THE OWNER.

CARELESS INSTALLATION AND OPERATION CAN RESULT IN SERIOUS INJURY OR EQUIPMENT DAMAGE.

Injury hazard

Failure to observe these instructions could lead to severe injury or death.

Always remove jewelry and wear eye protection.
Always use appropriate and adequate care in lifting components into place.
Always insure components will remain secure during installation and operation.
Always wear safety glasses when installing this kit
Always use extreme caution when cutting and trimming during fitting.
Always tighten all nuts and bolts securely per installation instructions.
Always perform regular inspections and maintenance on mounts and
related hardware





Rear Fender Base SKU: JK1001

2007-2015 Jeep JK 4 Door

Overview

Congratulations on the purchase of your new Fab Fours rear fender base assembly.

Your fenders were designed in 3-D from digitized data, CNC laser cut, fabricated, and powder coated... all in the U.S.A. Enjoy the fit and finish of a quality rear fender from Fab Fours, Inc.







Rear Fender Base SKU: JK1001

2007-2015 Jeep JK 4 Door

I. Tools Required

- Allen wrenches
- Socket set and wrenches
- Drill
- 1/4" & 17/32" drill bits
- Anti-seize (recommended)

NOTE: REAR BUMPER MUST BE REMOVED BEFORE YOU PROCEED. REMOVAL INSTRUCTIONS CAN BE FOUND AT FABFOURS.COM UNDER Y1251 INSTALLATION MANUAL.

II. Factory Fender Removal

(Perform these steps for both sides.)






Rear Fender Base SKU: JK1001

2007-2015 Jeep JK 4 Door

1. Remove Christmas tree clips located in the inner fender. Locations shown below.



- **2.** Once clips are removed. Start by firmly grasping the rear of fender flare and pulling flare outward towards you. (This may take a decent amount of pressure.)
- **3.** Once stock flare is off the vehicle, using a "push pin" tool remove the remaining clips that did not come out with the stock flare.








Rear Fender Base SKU: JK1001

2007-2015 Jeep JK 4 Door

III. Fab Fours Fender Base Installation

1. Start by lining the forward most mounting slot of fender with existing hole in pinch seam of jeep. Making sure that the fender and the body of the vehicle are lined up and flush bolt of the fender to the vehicle. See below.



2. With front bolt tight, line up the bottom rear mounting point of fender. Making sure fender is still aligned and flush to vehicle using ¼"drill bit, drill through rear mounting point into pinch seam of jeep first, then drill front. Using provided M6 hardware secure the rear of fender to vehicle.







Rear Fender Base SKU: JK1001

2007-2015 Jeep JK 4 Door

3. With fender base held in place, using a transfer punch, mark the center of the mounting holes. Once holes are marked, remove fender base.



4. Once fender is removed, you can begin drilling. Start out by drilling all punch marks with the $\frac{1}{4}$ " drill bit. Follow behind that with the $\frac{1}{1}$ 32" drill bit.







Rear Fender Base SKU: JK1001

2007-2015 Jeep JK 4 Door

5. With all the holes drilled out to 17/32" you can now begin installing rivet nuts with provided rivet nut tool. See below.



- **6.** Once all rivet nuts are installed you can install the fender base. Start by re-installing the M-6 hardware into the pinch seam of jeep. This will hold the fender on vehicle while you install the rest of the hardware.
- 7. Install the two rear bolts first, then install the recessed bolt as shown below. Once recessed bolt is installed you must tighten at this time, as the fender skin will cover it.



8. With the recessed bolt tightened you can now install the fender skin and remaining hardware. Start by lining up the mounting holes on the fender skin with the mounting holes on





Rear Fender Base SKU: JK1001

2007-2015 Jeep JK 4 Door

the fender base. Install all short bolts in location shown below to help hold fender skin in place.



9. With fender skin held in place you can now install remaining hardware into fender. Once all hardware is loosely installed you can tighten all hardware securing the fender to the vehicle.

Repeat steps 1 through 9 to install other side.

